





Keyless Bushing EDE.EEE

EDE



EEE



Material : S45C

M : Metric Screw

TS : Screw Bolt Tightening Torque

T : Max Torque

F : Allowable Thrust Load

P : Side Surface Pressure of Hub



TYPE	EDE.EEE								EDE	EEE	EDE.EEE			
	d	D	D1	B	A	W	L	M	Ts	T	F	P ₂		
	mm	mm	mm	mm	mm	mm	mm	mm					Nm	Nm
EDE	06	6	19	21.5	10.5	8	13.5	16.5	M3	2.3	3	6.2	4	53
	08	8	22	25	13	10	17	21	M4	3.9	5	18	4.7	70
	09	9	23	26	13	10	17	21	M4	3.9	5	21	4.7	68
	10	10	24	27	13	10	17	21	M4	3.9	5	30	6.2	87
	11	11	25	28	13	10	17	21	M4	3.9	5	34	6.2	84
	12	12	26	29	13	10	17	21	M4	3.9	5	47	7.8	100
	13	13	27	30	13	10	17	21	M4	3.9	5	50	7.8	97
	14	14	31	34	16	12.5	21	26	M5	8	11	70	10	87
	15	15	32	35	16	12.5	21	26	M5	8	11	75	10	84
	16	16	33	36	16	12.5	21	26	M5	8	11	80	10	81
	17	17	34	37	16	12.5	21	26	M5	8	11	105	12.5	99
	18	18	35	38	16	12.5	21	26	M5	8	11	110	12.5	96
	19	19	47	56	22	17	28	34	M6	14	17	290	30	94
	20	20	47	56	22	17	28	34	M6	14	17	320	32	100
	22	22	47	56	22	17	28	34	M6	14	17	320	32	100
	24	24	50	59	22	17	28	34	M6	14	17	360	32	100
	25	25	50	59	22	17	28	34	M6	14	17	420	34	100
	28	28	55	64	22	17	28	34	M6	14	17	500	34	100
	30	30	55	64	22	17	28	34	M6	14	17	520	34	100
	32	32	60	69	22	17	28	34	M6	14	17	770	48	110
35	35	60	69	22	17	28	34	M6	14	17	840	48	110	
38	38	65	74	22	17	28	34	M6	14	17	910	48	110	
40	40	65	74	22	17	28	34	M6	14	17	960	48	110	
42	42	75	84	22	17	28	34	M6	14	17	1000	65	110	
45	45	75	84	22	20	68	80	M12	145	145	1500	65	110	
48	48	80	89	25	20	68	80	M12	145	145	2000	85	140	
50	50	80	89	25	20	76	90	M14	190	190	2100	85	140	
55	55	85	91	25	20	76	90	M14	190	190	2500	95	140	
60	60	90	99	25	20	76	90	M14	190	190	2700	90	130	
65	65	95	104	25	20	76	90	M14	190	190	3200	100	140	
70	70	110	119	30	24	40	50	M10	70	83	4900	140	140	
75	75	115	124	30	24	40	50	M10	70	83	5300	140	130	
80	80	120	129	30	24	40	50	M10	70	83	5600	140	130	
85	85	125	134	30	24	40	50	M10	70	83	6700	160	130	
90	90	130	139	30	24	40	50	M10	70	83	7100	160	130	
95	95	135	144	30	24	40	50	M10	70	83	9100	195	135	
100	100	145	154	32	26	44	56	M12	125	145	10200	200	150	
110	110	155	164	32	26	44	56	M12	125	145	10600	200	150	
120	120	165	174	32	26	44	56	M12	125	145	13000	216	140	
130	130	180	189	40	34	54	64	M12	125	145	18900	290	135	
140	140	190	199	40	34	54	68	M14	190	230	20500	333	125	
150	150	200	209	40	34	54	68	M14	190	230	25000	362	120	
160	160	210	219	40	34	54	68	M14	190	230	29000	362	130	
170	170	225	234	50	44	64	78	M14	190	230	34000	400	135	
180	180	235	244	50	44	64	78	M14	190	230	36000	400	120	
190	190	250	259	50	44	64	78	M14	190	230	47500	500	115	
200	200	260	269	50	44	64	78	M14	190	230	50000	500	140	

Order TYPE
訂貨代號 EDE-20

PS1 : if you need another exceptional to process the specifications form, please contact us.